

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WELLSEAL JOINING COMPOUND

Product code: 865640

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Non setting jointing compound

1.3. Details of the supplier of the safety data sheet

Company name: Quest Consumables Ltd
Stock House, Seymour Road,
Nuneaton, Warwickshire
CV11 4LB
United Kingdom

Tel: +44 02476 322126

Fax: +44 02476 322117

Email: sales@questconsumables.com

1.4. Emergency telephone number 0044 1895465600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R40; Sens.: R43; N: R51/53

Classification under CLP: Carc. 2: H351; Aquatic Chronic 2: H411; Skin Sens. 1: H317

Most important adverse effects: Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



SAFETY DATA SHEET

WELLSEAL JOINING COMPOUND

Page: 2

Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P281: Use personal protective equipment as required.
P308+313: IF exposed or concerned: Get medical advice/attention.

Label elements under CHIP:

Hazard symbols: Dangerous for the environment.
Harmful.



Risk phrases: R40: Limited evidence of a carcinogenic effect.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S36/37: Wear suitable protective clothing and gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PERCHLOROETHYLENE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|----------|---------------------|--|---------|
| 204-825-9 | 127-18-4 | Xn: R40; N: R51/53 | Carc. 2: H351; Aquatic Chronic 2: H411 | 40-50% |

PULVERISED VINSOL RESIN

| | | | | |
|---|---|------------|---|-------|
| - | - | Sens.: R43 | - | 3-10% |
|---|---|------------|---|-------|

[cont...]

SAFETY DATA SHEET

WELLSEAL JOINING COMPOUND

Page: 3

PROPAN-2-OL

| | | | | |
|-----------|---------|-------------------------|--|------|
| 200-661-7 | 67-63-0 | F: R11; Xi: R36; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336 | 1-3% |
|-----------|---------|-------------------------|--|------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be loss of consciousness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur. There may be loss of consciousness.

Delayed / immediate effects: Headaches or general malaise may result. Delayed effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Water. Carbon dioxide. Alcohol or polymer foam.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of hydrogen chloride / phosgene.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

[cont...]

SAFETY DATA SHEET
WELLSEAL JOINING COMPOUND

Page: 4

6.2. Environmental precautions

Environmental precautions: Contain the spillage using bunding. Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PERCHLOROETHYLENE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|-----------------------|-----------------------|------------|--------------|
| UK | 345 mg/m ³ | 689 mg/m ³ | - | - |

PROPAN-2-OL

| | | | | |
|----|-----------------------|------------------------|---|---|
| UK | 999 mg/m ³ | 1250 mg/m ³ | - | - |
|----|-----------------------|------------------------|---|---|

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Breathing protection is required in inadequately ventilated places.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Impermeable protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

[cont...]

SAFETY DATA SHEET
WELLSEAL JOINING COMPOUND

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Dark brown

Odour: Characteristic odour

Boiling point/range°C: 121

Relative density: 1.26

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Flames. Hot surfaces.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong bases. Sodium. Potassium.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon monoxide. In combustion emits toxic fumes of hydrogen chloride / phosgene.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

PERCHLOROETHYLENE

| | | | | |
|-----|-----|------|------|-------|
| IPR | RAT | LD50 | 4678 | mg/kg |
| ORL | MUS | LD50 | 8100 | mg/kg |
| ORL | RAT | LD50 | 2629 | mg/kg |

[cont...]

SAFETY DATA SHEET
WELLSEAL JOINING COMPOUND

Page: 6

PROPAN-2-OL

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 1088 | mg/kg |
| ORL | MUS | LD50 | 3600 | mg/kg |
| ORL | RAT | LD50 | 5045 | mg/kg |
| SCU | MUS | LDLO | 6 | gm/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|---------------|-------|-----------------------|
| Sensitisation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be loss of consciousness.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur. There may be loss of consciousness.

Delayed / immediate effects: Headaches or general malaise may result. Delayed effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water. Vapour is heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.

Section 13: Disposal considerations

[cont...]

SAFETY DATA SHEET
WELLSEAL JOINING COMPOUND

Page: 7

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(PERCHLOROETHYLENE)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

[cont...]

SAFETY DATA SHEET
WELLSEAL JOINING COMPOUND

Page: 8

Phrases used in s.2 and 3: H225: Highly flammable liquid and vapour.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H411: Toxic to aquatic life with long lasting effects.
R11: Highly flammable.
R36: Irritating to eyes.
R40: Limited evidence of a carcinogenic effect.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

ENVIRONMENTAL CARE: Please do not dispose of uncured material. If disposing please mix any waste product to its cured state.