

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

865655 Loctite Chemical Metal

Contains:

Styrene

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2K Filler paste

1.3. Details of the supplier of the safety data sheet

Quest Consumables Ltd
Stock House, Seymour Road
Nuneaton, Warwickshire
CV11 4LB

Phone: +44 2476 322126

Fax-no.: +44 2476 322117

sales@questconsumables.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapor.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Toxic to reproduction	Category 2
H361d Suspected of damaging the unborn child.	
Specific target organ toxicity - repeated exposure	Category 1
H372 Causes damage to organs through prolonged or repeated exposure.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Signal word:**

Danger

Hazard statement:

H226 Flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H361d Suspected of damaging the unborn child.

Precautionary statement:

For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapours.
 P281 Use personal protective equipment as required.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of water.
 P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Sealant

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Styrene 100-42-5	202-851-5 01-2119457861-32	10- 20 %	Flam. Liq. 3 H226 Acute Tox. 4 H332 Asp. Tox. 1 H304 Eye Irrit. 2 H319 Skin Irrit. 2 H315 STOT RE 1; Inhalation H372 Repr. 2 H361d Aquatic Chronic 3 H412 STOT SE 3 H335

For full text of the H - statements and other abbreviations see section 16 "Other information".
 Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

In case of fire, keep containers cool with water spray.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional information:

Do not inhale vapors and fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition.

Ensure adequate ventilation.

Wear protective equipment.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

For small spills wipe up with paper towel and place in container for disposal.

Wash spillage site thoroughly with soap and water or detergent solution.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not inhale vapors and fumes.
Avoid skin and eye contact.
Keep away from sources of ignition - no smoking.
Use only in well-ventilated areas.
See advice in section 8
Avoid open flames and sources of ignition.
No smoking.

Hygiene measures:

Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from sources of ignition.
Store in a cool, well-ventilated place.

7.3. Specific end use(s)

2K Filler paste

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Styrene 100-42-5 [STYRENE]	250	1.080	Short Term Exposure Limit (STEL):		EH40 WEL
Styrene 100-42-5 [STYRENE]	100	430	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [ROUGE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [ROUGE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [IRON OXIDE, FUME (AS FE)]		5	Time Weighted Average (TWA):		EH40 WEL
Diiron trioxide 1309-37-1 [IRON OXIDE, FUME (AS FE)]		10	Short Term Exposure Limit (STEL):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, RESPIRABLE DUST]		0,8	Time Weighted Average (TWA):		IR_OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Styrene 100-42-5 [STYRENE]	40	170	Short Term Exposure Limit (STEL):		IR_OEL

Styrene 100-42-5 [STYRENE]	20	85	Time Weighted Average (TWA):		IR_OEL
Diiron trioxide 1309-37-1 [IRON OXIDE, FUME (AS FE)]		10	Short Term Exposure Limit (STEL):		IR_OEL
Diiron trioxide 1309-37-1 [ROUGE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Diiron trioxide 1309-37-1 [ROUGE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Diiron trioxide 1309-37-1 [IRON OXIDE, FUME (AS FE)]		5	Time Weighted Average (TWA):		IR_OEL

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Ensure adequate ventilation.

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	paste pasty grey
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	> 100,0 °C (> 212 °F)
Flash point	32 °C (89.6 °F); no method
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density (23 °C (73.4 °F))	1,6700 g/cm ³
Bulk density	No data available / Not applicable
Viscosity (Physica Rheolab)	1.200 - 4.200 pa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (23 °C (73.4 °F); Solvent: Water)	Insoluble
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used properly.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoidStable under normal conditions of storage and use.
Heat, flames, sparks and other sources of ignition.**10.5. Incompatible materials**

See section reactivity

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

STOT-repeated exposure:

Causes damage to organs through prolonged or repeated exposure.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Reproductive toxicity:

Suspected of damaging the unborn child.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Styrene 100-42-5	LD50	6.600 - 8.000 mg/kg	oral		rat	

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Styrene 100-42-5	LC50	11,8 mg/l		4 h	rat	

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Styrene 100-42-5	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Styrene 100-42-5	not sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Styrene 100-42-5	positive	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Styrene 100-42-5	negative	inhalation: vapour		mouse	

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure time/Frequency of treatment	Route of application	Method
Styrene 100-42-5	not carcinogenic	rat	male/female	104 w 6 h/d, 5 d/w	inhalation: vapour	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Styrene 100-42-5	LOAEL=2.000 mg/kg	oral: gavage	daily (5 d/w)	rat	
Styrene 100-42-5	NOAEL=1.000 mg/kg	oral: gavage	daily (5 d/w)	rat	
Styrene 100-42-5		inhalation: vapour	4 w/6 h/d, 5 d/w	rat	

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Styrene 100-42-5	LC50	10 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Styrene 100-42-5	EC50	4,7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Styrene 100-42-5	EC10	0,28 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
	EC50	6,3 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Styrene 100-42-5	EC 50	500 mg/l	Bacteria	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Styrene 100-42-5	NOEC	1,01 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

12.2. Persistence and degradability**Persistence and Biodegradability:**

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method

Styrene 100-42-5	readily biodegradable	aerobic	87 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
---------------------	-----------------------	---------	------	---

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Bioaccumulative potential:**

No data available for the product.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Styrene 100-42-5 Styrene 100-42-5	2,96	74			25 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Styrene 100-42-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Incineration under controlled conditions is recommended.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information**14.1. UN number**

ADR	2055
RID	2055
ADN	2055
IMDG	2055
IATA	2055

14.2. UN proper shipping name

ADR	STYRENE MONOMER, STABILIZED (solution)
RID	STYRENE MONOMER, STABILIZED (solution)
ADN	STYRENE MONOMER, STABILIZED (solution)
IMDG	STYRENE MONOMER, STABILIZED (solution)
IATA	Styrene monomer, stabilized (solution)

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

When transporting as a set (component A and B) then the following dangerous good classification is used: UN 3269 Polyester resin kit, 3, III.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content (2010/75/EC)	14,8 %
-----------------------------	--------

VOC Paints and Varnishes (EU):

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	Bodyfiller/stopper
Phase I (from 1.1.2007):	250 g/l
max. VOC content:	130 g/l

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

Xn - Harmful



Risk phrases:

R10 Flammable.

R20 Harmful by inhalation.

R36/38 Irritating to eyes and skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child.

Safety phrases:

S2 Keep out of the reach of children.

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour.

S28 After contact with skin, wash immediately with plenty of water and soap.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37 Wear suitable protective clothing and gloves.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

Styrene

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.