



## SAFETY DATA SHEET

### FIXT Flammable Air Duster

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name                      FIXT Flammable Air Duster  
 Product number                  FX081210

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses                      Duster Spray

##### 1.3. Details of the supplier of the safety data sheet

Supplier                                Seymour Road  
     Nuneaton  
     Warwickshire  
     CV11 4LB

    02476 322 196 (T)  
     02476 322 117 (F)  
     info@fixtconsumables.com

##### 1.4. Emergency telephone number

Emergency telephone              02476 322 196

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification

Physical hazards                      Aerosol 1 - H222, H229  
 Health hazards                        Not Classified  
 Environmental hazards                Not Classified

Classification (67/548/EEC or 1999/45/EC)    F+;R12.

**Human health**                        Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Environmental**                        This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment

**Physicochemical**                      Not considered to be a significant hazard due to the small quantities used. Aerosol containers can explode when heated, due to excessive pressure build-up.

##### 2.2. Label elements

###### Pictogram



Signal word                              Danger

## FIXT Flammable Air Duster

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with local regulations. P260 Do not breathe vapour/spray. P271 Use only outdoors or in a well-ventilated area.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>	<b>60-100%</b>
CAS number: 68476-85-7	EC number: 270-704-2
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46
Press. Gas, Liquefied - H280	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once.
<b>Inhalation</b>	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water.
<b>Skin contact</b>	Rinse with water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Rinse with water. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Water spray, foam, dry powder or carbon dioxide. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.
-------------------------------------	---

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

## FIXT Flammable Air Duster

### 5.3. Advice for firefighters

**Protective actions during firefighting** Warn firefighters that aerosols are involved. Containers close to fire should be removed or cooled with water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** VENTILATE/EVAPORATE.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 degrees Centigrade. Do not pierce or burn, even after use.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### **PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

### 8.2. Exposure controls

**Appropriate engineering controls** This product must not be handled in a confined space without adequate ventilation.

**Personal protection** When using the aerosol do not smoke.

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

**Hand protection** Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

**Other skin and body protection** Not relevant

## FIXT Flammable Air Duster

**Hygiene measures**                    The product itself does not pose any hygiene risks. However normal hygiene standards appropriate to the work place should be maintained.

**Respiratory protection**            If ventilation is inadequate, suitable respiratory protection must be worn.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Colourless.
<b>Odour</b>	No characteristic odour.
<b>Initial boiling point and range</b>	-40 to -2°C @ 1013 hPa
<b>Flash point</b>	<-40°C
<b>Upper/lower flammability or explosive limits</b>	Lower : 1.8% - Upper 9.5%
<b>Vapour pressure</b>	ca. 590 to 1760 kPa @ 45°C
<b>Vapour density</b>	ca. 1.5 at 15°C
<b>Relative density</b>	0.533 @ °C
<b>Partition coefficient</b>	log Pow: ca. 2.3 to 2.8
<b>Auto-ignition temperature</b>	410-580°C
<b>Comments</b>	Information given is applicable to the major ingredient.

#### 9.2. Other information

<b>Other information</b>	Not available.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 533 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity**                            Stable at normal ambient temperatures and when used as recommended.

#### 10.2. Chemical stability

**Stability**                                Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions**    Does not decompose when used and stored as recommended.

#### 10.4. Conditions to avoid

**Conditions to avoid**                Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

**Materials to avoid**                 Keep away from oxidising materials, heat and flames.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products**    Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

## FIXT Flammable Air Duster

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

<b>General information</b>	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
<b>Inhalation</b>	May cause respiratory system irritation.
<b>Ingestion</b>	No specific health hazards known.
<b>Skin contact</b>	Skin irritation should not occur when used as recommended.
<b>Eye contact</b>	Irritating to eyes.
<b>Acute and chronic health hazards</b>	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
<b>Route of entry</b>	Inhalation
<b>Target organs</b>	Respiratory system, lungs
<b>Medical symptoms</b>	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

### SECTION 12: Ecological Information

**Ecotoxicity** The product is not expected to be hazardous to the environment.

#### 12.1. Toxicity

**Toxicity** Not available.

#### 12.2. Persistence and degradability

**Persistence and degradability** Not available.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Not available.

**Partition coefficient** log Pow: ca. 2.3 to 2.8

#### 12.4. Mobility in soil

**Mobility** Not known.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** Not available.

#### 12.6. Other adverse effects

**Other adverse effects** Not available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Do not puncture or incinerate, even when empty.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

## FIXT Flammable Air Duster

### General

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1

#### Transport labels



#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

EmS	F-D, S-U
Tunnel restriction code	(D)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## FIXT Flammable Air Duster

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Commission Regulation (EU) No 453/2010 of 20 May 2010.
<b>Guidance</b>	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Revision comments</b>	Supplemental information added.
<b>Revision date</b>	18/11/2015
<b>Revision</b>	2
<b>SDS number</b>	12405
<b>SDS status</b>	Approved.
<b>Risk phrases in full</b>	R12 Extremely flammable.
<b>Hazard statements in full</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.