



SAFETY DATA SHEET BATTERY PROTECTOR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BATTERY PROTECTOR

Product number X61550

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier Quest Consumables Ltd
Stock House, Seymour Road
Nuneaton
Warwickshire
CV11 4LB
02476 322 196 (T)
02476 322 117 (F)
sales@forceproducts.com

1.4. Emergency telephone number

Emergency telephone 02476 322 196

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards STOT SE 3 - H336 STOT RE 1 - H372

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) F+;R12. N;R51/53. R66,R67.

Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word

Danger

BATTERY PROTECTOR

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H336 May cause drowsiness or dizziness. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P260 Do not breathe vapour/spray. P501 Dispose of contents/container in accordance with local regulations.
Supplemental label information	RCH002b For professional users only.
Contains	White Spirit (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics, PROPAN-2-OL

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics 30-60%		
CAS number: 64742-88-7	EC number: 919-446-0	REACH registration number: 01-2119458049-33
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. N;R51/53. R10,R66,R67.	
BUTANE 10-30%		
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: Exempt under REACH
Classification Flam. Gas 1 - H220	Classification (67/548/EEC or 1999/45/EC) F+;R12	
ISOBUTANE 5-10%		
CAS number: 75-28-5	EC number: 200-857-2	REACH registration number: Exempt under REACH
Classification Flam. Gas 1 - H220	Classification (67/548/EEC or 1999/45/EC) F+;R12	

BATTERY PROTECTOR

PROPANE		5-10%
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: Exempt under REACH
Classification Flam. Gas 1 - H220	Classification (67/548/EEC or 1999/45/EC) F+;R12	

PROPAN-2-OL		1-5%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

5.3. Advice for firefighters

BATTERY PROTECTOR

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): WEL 800 ppm

Short-term exposure limit (15-minute): WEL No std.

PROPANE

Long-term exposure limit (8-hour TWA): SUP 1000 ppm

Short-term exposure limit (15-minute): SUP 1250 ppm

BATTERY PROTECTOR

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics (CAS: 64742-88-7)

DNEL

Industry - Inhalation; Short term systemic effects: 570 mg/m³
 Industry - Dermal; Long term systemic effects: 1056 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 1980 mg/m³
 Consumer - Inhalation; Short term systemic effects: 570 mg/m³
 Consumer - Dermal; Long term systemic effects: 26 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 71 mg/m³
 Consumer - Oral; Long term systemic effects: 26 mg/kg/day
 Workers - Inhalation; Long term systemic effects: 330 mg/m³
 Workers - Dermal; Long term systemic effects: 44 mg/kg/day

PROPANE (CAS: 74-98-6)

Ingredient comments SUP = Supplier's recommendation.

PROPAN-2-OL (CAS: 67-63-0)

DNEL

Industry - Dermal; Long term systemic effects: 888 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 500 mg/m³
 Consumer - Dermal; Long term systemic effects: 319 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 26 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 89 mg/m³

PNEC

- Fresh water; 140.9 mg/l
- Marine water; 140.9 mg/l
- Intermittent release; 140.9 mg/l
- Sediment (Freshwater); 552 mg/kg
- Sediment (Marinewater); 552 mg/kg
- STP; 2251 mg/l
- Soil; 28 mg/kg

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.
Personal protection	When using do not smoke.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.
Hand protection	Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

BATTERY PROTECTOR

Hygiene measures Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Orange.
Odour	Organic solvents.
Flash point	<-40°C
Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 448 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability Avoid the following conditions: Heat, sparks, flames.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

BATTERY PROTECTOR

Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Route of entry	Inhalation
Target organs	Central nervous system Respiratory system, lungs
Medical symptoms	Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological Information

Ecotoxicity	This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.
--------------------	---

12.1. Toxicity

Toxicity	Not available.
-----------------	----------------

12.2. Persistence and degradability

Persistence and degradability	Not available.
--------------------------------------	----------------

12.3. Bioaccumulative potential

Bioaccumulative potential	Not available.
----------------------------------	----------------

12.4. Mobility in soil

Mobility	Not known.
-----------------	------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	Not available.
---	----------------

12.6. Other adverse effects

Other adverse effects	Not available.
------------------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

14.1. UN number

BATTERY PROTECTOR

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS (White Spirit)

Proper shipping name (IMDG) AEROSOLS (White Spirit)

Proper shipping name (ICAO) AEROSOLS (White Spirit)

Proper shipping name (ADN) AEROSOLS (White Spirit)

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID subsidiary risk

ADR/RID label 2.1

IMDG class 2.1

IMDG subsidiary risk

ICAO class/division 2.1

ICAO subsidiary risk

Transport labels



14.4. Packing group

Not applicable.

ADR/RID packing group

IMDG packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

Emergency Action Code

Hazard Identification Number (ADR/RID)

Tunnel restriction code (D)

BATTERY PROTECTOR

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplemental information added.
Revision date	12/05/2015
Revision	2
SDS number	10577
SDS status	Approved.
Risk phrases in full	R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R36 Irritating to eyes. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.

BATTERY PROTECTOR

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H229 Pressurised container: may burst if heated
H304 May be fatal if swallowed and enters airways.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.